


# KANI 3 RD



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO349WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 950mA 37V	40W	3000K	3870 Lm	3582 Lm
DO349NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 950mA 37V	40W	4000K	4055 Lm	3770 Lm



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (130mm)



Beam 40°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.



Connect to a constant current Led power supply of 950mA DC.




The product is dimmable (0-10V).




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.