


KARL 2 RDX

- 3 in 1 adjustable round semi-recessed spotlight.
- 3000K, 3500K or 4000K as desired via a switch at the back of the luminaire.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO54305	MATT BLACK	ALUMINIUM	AC 230V	DC 600mA 36V	26W	3000-3500-4000K	2750 Lm (4000K)	2250 Lm (4000K)
DO54330	MATT WHITE	ALUMINIUM	AC 230V	DC 600mA 36V	26W	3000-3500-4000K	2750 Lm (4000K)	2250 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 1 Joule.



Earth wire . Fixture equipped with primary insulation only.



Hole cut to insert luminaire. (120mm)



Minimum ceiling height to insert luminaire. (110mm)



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 355°.



Beam 38°.



3 CCT.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.





Power supply included.



Connect to a constant current Led power supply of 600mA DC.




The product is dimmable.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.