

68

System Lumen

KO 703R

- Round ecorative wall recessed fixture for corridor lighting.
 Protective glass.
- Recessed box included.

CODE

- Non-dimmable converter built in the device.

MATERIAL

This product contains 1 light source(s) of energy efficiency E.



T° (K)



Ø92

LED Lumen

| K0703R | ALUMINIUM | AC 230V | DC 350mA 3V | 1W | 3000K | 120 Lm | 56 Lm |
|-----------------------|------------------------------------|-------------------------|------------------------|-----------------|-------|--------|-------|
| Recess | ed wall mounting only. | | | | | | |
| Indoor u | use only. | | | | | | |
| | ed against the ingress of s | olid bodies greater th | an 1mm. Protected ag | ainst splashing | | | |
| IK Protect | ion against an impact ener | gy of 0,20 Joule. | | | | | |
| Live pa insulation | rts are equipped with addit on. | ional isolation protect | ion, such as reinforce | d or double | | | |
| Hole cu | it to insert luminaire (82 mr | n) | | | | | |
| | t in conformity CE. | | | | | | |
| CRI CRI>80 |) | | | | | | |
| | ecifications. | | | | | | |
| | iological risk RG1 | | | | | | |
| 650° Test on | 1 650°. | | | | | | |
| Power : | supply included. | | | | | | |
| | et to a constant current Led | l power supply of 350 | mA DC. | | | | |
| | warranty. | | | | | | |
| | | | | | | | |
| | Replaceable LED light so | urce by an electrician | | | | | |
| | Replaceable control gear | by an electrician. | | | | | |

DC

LED

AC