


KORY R

RE
2020



- 3 in 1 fixed round recessed downlight.
- 2700K, 3000K or 4000K as desired via a switch in the luminaire.
- Fastened with springs.
- Can be covered with peeled or blown insulation, converter included.
- Automatic double terminal block.
- Remote non-dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO54905	MATT BLACK	ALU.+COMPOSITE	AC 230V	DC 230mA 21V	6W	2700-3000-4000K	775 Lm (4000K)	620 Lm (4000K)
DO54930	MATT WHITE	ALU.+COMPOSITE	AC 230V	DC 230mA 21V	6W	2700-3000-4000K	775 Lm (4000K)	665 Lm (4000K)



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 2 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (68mm)



Beam 60°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.



LED specifications.



Photobiological risk RG1



In compliance with current thermal regulation (France).



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)




Class II power supply included.





Connect to a constant current Led power supply of 230mA DC.



5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Non-replaceable light source.