

## KOS 2 S

- Wall lamp for outdoor lighting.
- Glass diffusers.

CODE

÷ 🗱 💿

- Up and down lighting.With cable inlet and outlet.
- Non dimmable converter built in the device.

COLOR

This product contains 2 light source(s) of energy efficiency F.


MATERIAL

AC

LED



T° (K)



System Lumen

LED Lumen

					- ()		-,
OU478WW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	2x6W	3000K	2x685 Lm	2x575 Lm
Wall mou	nting only. This lamp	illuminates on 2 areas.					
Outdoor u	ISE.						
Protected 65	against the ingress o	of dust. Protected against jet	s of water.				
<b>IK</b> 06	n against an impact e	energy of 1 Joule.					
$\boxed{\underline{}}$ Earth wire	e. Fixture equipped w	vith primary insulation only.					
Beam 80°							
	n conformity CE.						
CRI CRI>80							
LED LED spec	ifications.						
	ogical risk RG1						
650° Test on 6	50°.						
Power su	oply included.						
3 years w	arranty.						
	ric data available on	our website: www.indigo-ligh	nting.com				
	enlaceable control o	ear by an electrician.					
2300							
🔆 🗱 💿 🕺	on-replaceable light	source.					