


# LASER RDX



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO336SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	2700K	930 Lm	690 Lm
DO336SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	2700K	930 Lm	725 Lm
DO336WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	1050 Lm	780 Lm
DO336WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	3000K	1050 Lm	820 Lm
DO336NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	1100 Lm	815 Lm
DO336NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 500mA 18V	9W	4000K	1100 Lm	860 Lm



NOIR MAT



BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,50 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (70mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 20°.



Product in conformity CE.



Colour rendering index >95.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.





Product can not be covered after installation even with insulation.





Class II power supply included.





 Connect to a constant current Led power supply of 500mA DC.

 The product is dimmable.

 5 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable LED light source by an electrician.

 Replaceable control gear by an electrician.