


LASY RX

- Adjustable round recessed spotlight.
- Fastened with springs.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Remote non-dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO334WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 3V	1W	3000K	100 Lm	90 Lm
DO334WW25	SATIN ALUMINIUM	CAST ALUMINIUM	AC 230V	DC 350mA 3V	1W	3000K	100 Lm	90 Lm
DO334WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 3V	1W	3000K	100 Lm	90 Lm





















MATT BLACK




SATIN ALUMINIUM




MATT WHITE

-  Recessed ceiling mounting only.
-  Indoor use only.
-  IP 44 Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.
-  IK 04 Protection against an impact energy of 0,50 Joule.
-  Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.
-  Hole cut to insert luminaire (42 mm)
-  The luminaire can be adjusted vertically up to a maximum of 30°.
-  Beam 24°.
-  Product in conformity CE.
-  CRI >80
-  LED L70B50 50.000h LED specifications.
-  RG1 Photobiological risk RG1
-  650° Test on 650°.
-  Product can be covered after installation with insulation. (not blown)
-  Class II power supply included.
-  350 mA Connect to a constant current Led power supply of 350mA DC.
-  5 5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.



Replaceable control gear by an electrician.