

LEGA D

- Linear structure for 48 V track.
- Dimmable DALI.

This product contains 1 light source(s) of energy efficiency G.



| CODE | COLOR | MATERIAL | DC | LED | T° (K) | LED Lumen | System Lumen |
|-------------|------------|-----------|--------|-----|--------|-----------|--------------|
| TR364WW05DA | MATT BLACK | ALUMINIUM | DC 48V | 23W | 3000K | 2850 Lm | 1737 Lm |
| TR364NW05DA | MATT BLACK | ALUMINIUM | DC 48V | 23W | 4000K | 2950 Lm | 1814 Lm |



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Beam 110°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG1



Test on 650°.



Connect to a constant voltage LED power supply of 48VDC.




The product is dimmable (DALI input).



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.