


LENA

- Adjustable square recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied (DALI versions: converter with push-dim function).



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
PHASE CUT DIMMABLE									
DO386SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	386 Lm	24°
DO386SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	386 Lm	24°
DO386WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	414 Lm	24°
DO386WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	414 Lm	24°
DO386NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	447 Lm	24°
DO386NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	447 Lm	24°
DO385SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	372 Lm	36°
DO385SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	372 Lm	36°
DO385WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	417 Lm	36°
DO385WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	417 Lm	36°
DO385NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	495 Lm	36°
DO385NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	495 Lm	36°
DALI DIMMABLE									
DO386SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	386 Lm	24°
DO386SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	386 Lm	24°
DO386WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	414 Lm	24°
DO386WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	414 Lm	24°
DO386NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	447 Lm	24°
DO386NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	447 Lm	24°
DO385SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	372 Lm	36°
DO385SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	2700K	680 Lm	372 Lm	36°
DO385WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	417 Lm	36°
DO385WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	3000K	700 Lm	417 Lm	36°
DO385NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	495 Lm	36°
DO385NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 700mA 9V	7W	4000K	720 Lm	495 Lm	36°



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Square piercing to insert the luminaire. (78x78mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Horizontal orientation maximum to 355°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.



Connect to a constant current Led power supply of 700mA DC.



The product is dimmable.



5 years warranty.



Photometric data available on our website: www.indigo-lighting.com