


# LENA POWER

- Adjustable square recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied (DALI versions: converter with push-dim function).



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen	α
<b>PHASE CUT DIMMABLE</b>									
DO401SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	784 Lm	15°
DO401SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	784 Lm	15°
DO401WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	941 Lm	15°
DO401WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	941 Lm	15°
DO401NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	993 Lm	15°
DO401NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	993 Lm	15°
DO402SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	688 Lm	30°
DO402SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	688 Lm	30°
DO402WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	862 Lm	30°
DO402WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	862 Lm	30°
DO402NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	887 Lm	30°
DO402NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	887 Lm	30°
DO403SW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	807 Lm	50°
DO403SW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	807 Lm	50°
DO403WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	996 Lm	50°
DO403WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	996 Lm	50°
DO403NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	1010 Lm	50°
DO403NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	1010 Lm	50°
<b>DALI DIMMABLE</b>									
DO401SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	784 Lm	15°
DO401SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	784 Lm	15°
DO401WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	941 Lm	15°
DO401WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	941 Lm	15°
DO401NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	993 Lm	15°
DO401NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	993 Lm	15°
DO402SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	688 Lm	30°
DO402SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	688 Lm	30°
DO402WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	862 Lm	30°
DO402WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	862 Lm	30°
DO402NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	887 Lm	30°
DO402NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	887 Lm	30°
DO403SW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	807 Lm	50°
DO403SW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	2700K	1260 Lm	807 Lm	50°
DO403WW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	996 Lm	50°
DO403WW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	3000K	1300 Lm	996 Lm	50°
DO403NW05DA	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	1010 Lm	50°
DO403NW30DA	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 350mA 36V	13W	4000K	1340 Lm	1010 Lm	50°


MATT BLACK


MATT WHITE





**IP 23** Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.

**IK 02** Protection against an impact energy of 0,20 Joule.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Square piercing to insert the luminaire. (102x102mm)

 The luminaire can be adjusted vertically up to a maximum of 30°.

 Horizontal orientation maximum to 355°.

**CE** Product in conformity CE.


**CRI >90** CRI>90


**LED L90B10 50.000h** LED specifications.

**UGR <19** UGR below 19.

**RG1** Photobiological risk RG1

**850°** Test on 850°.


 Product can not be covered after installation even with insulation.

 Power supply included.

**350 mA** Connect to a constant current Led power supply of 350mA DC.

**DIM** The product is dimmable.

**5** 5 years warranty.

 Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)