


# LIMA 3 PLUS

- Spotlight for accent lighting.
- Adapter for Track III SURFACE.
- 2700K, 3000K or 4000K as desired via a switch at the back of the luminaire.
- Non dimmable converter built in the device.
- Use power glasses with a colour temperature of 3000K.
- Exposed base TR241 to be ordered separately.



This product contains 1 light source(s) of energy efficiency G.









CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	α
<b>40°</b>								
TR39905	MATT BLACK	ALUMINIUM	AC 230V	55W	2700-3000↔	4925 Lm (4000K)	3625 Lm (4000K)	40°
TR39930	MATT WHITE	ALUMINIUM	AC 230V	55W	2700-3000↔	4925 Lm (4000K)	3960 Lm (4000K)	40°
<b>60°</b>								
TR40005	MATT BLACK	ALUMINIUM	AC 230V	55W	2700-3000↔	4925 Lm (4000K)	3615 Lm (4000K)	60°
TR40030	MATT WHITE	ALUMINIUM	AC 230V	55W	2700-3000↔	4925 Lm (4000K)	3875 Lm (4000K)	60°



MATT BLACK



MATT WHITE

ACCESSOIRES	COLOR	DESCRIPTION	
TR32305	BLACK	HONEYCOMB DIA.100mm	
TR32632		GLASS FOR FOOD APPLICATION DIA.100mm	
TR32956		GLASS FOR FOOD APPLICATION DIA.100mm	
TR33258		BLADE LIGHT FILTER DIA.100mm	
TR38705	MATT BLACK	FLAP DIA.100mm	
TR38730	MATT WHITE	FLAP DIA.100mm	
TR24130	BLACK	SURFACE MOUNTED BASE	
TR24131	WHITE	SURFACE MOUNTED BASE	



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Product in conformity CE.



CRI>90



3 CCT.



LED specifications.



Photobiological risk RG1



Test on 850°.




Power supply included.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.