


LINEA 1

- Linear structure for diffuse lighting.
- Adapter for Track III SURFACE.
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR357WW05	BLACK	ALUMINIUM	AC 230V	30W	3000K	3750 lm	3188 Lm
TR357WW30	WHITE	ALUMINIUM	AC 230V	30W	3000K	3750 lm	3188 Lm
TR357NW05	BLACK	ALUMINIUM	AC 230V	30W	4000K	3900 Lm	3269 Lm
TR357NW30	WHITE	ALUMINIUM	AC 230V	30W	4000K	3900 Lm	3269 Lm





BLACK





WHITE


ACCESSOIRES	COLOR	DESCRIPTION
TR38805	BLACK	HONEY COMB 665X35mm





 Ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.


 Protection against an impact energy of 0,50 Joule.

 Earth wire . Fixture equipped with primary insulation only.


 Vertical orientation maximum to 90°.


 Horizontal orientation maximum to 350°.


 Beam 120°.


 Product in conformity CE.

 CRI>80


 LED specifications.


 Photobiological risk RG1


 Test on 650°.

 Power supply included.

3 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.