

LINEA 2

- Linear structure for diffuse lighting.
- Adapter for Track III SURFACE.
- Non-dimmable converter built in the device.

This product contains 2 light source(s) of energy efficiency D.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR358WW05	BLACK	ALUMINIUM	AC 230V	2x30W	3000K	2x3750 Lm	2x3188 Lm
TR358WW30	WHITE	ALUMINIUM	AC 230V	2x30W	3000K	2x3750 Lm	2x3188 Lm
TR358NW05	BLACK	ALUMINIUM	AC 230V	2x30W	4000K	2x3900 Lm	2x3269 Lm
TR358NW30	WHITE	ALUMINIUM	AC 230V	2x30W	4000K	2x3900 Lm	2x3269 Lm



BLACK



WHITE



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,50 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 120°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.




3 years warranty.




Photometric data available on our website: www.indigo-lighting.com





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.