


LINEAR 2 C

- Linear ceiling lamp.
- Prismatic PC diffuser.
- Multi-power : 21 or 32W as desired via a switch at the back of the luminaire.
- 3000K, 3500K or 4000K as desired via a switch at the back of the luminaire.
- Non dimmable
or dimmable DAL-push converter built in the device.
- Up to 25 luminaires can be connected on line.
- Mechanical linear connection to be ordered separately.
Fast electrical connections included in the luminaire.

This product contains 432 light source(s) of energy efficiency F(05), E(30).



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
CL10805	MATT BLACK	ALUMINIUM	AC 230V	21W 32W	3000-3500-4000K	3350 Lm (4000K) 5100 Lm (4000K)	2045 Lm (4000K) 2990 Lm (4000K)
CL10830	MATT WHITE	ALUMINIUM	AC 230V	21W 32W	3000-3500-4000K	3350 Lm (4000K) 5100 Lm (4000K)	2560 Lm (4000K) 3740 Lm (4000K)
CL10805DA	MATT BLACK	ALUMINIUM	AC 230V	21W 32W	3000-3500-4000K	3350 Lm (4000K) 5100 Lm (4000K)	2045 Lm (4000K) 2990 Lm (4000K)
CL10830DA	MATT WHITE	ALUMINIUM	AC 230V	21W 32W	3000-3500-4000K	3350 Lm (4000K) 5100 Lm (4000K)	2560 Lm (4000K) 3740 Lm (4000K)



MATT BLACK



MATT WHITE

ACCESSOIRES	COLOR	MATERIAL	DESCRIPTION
CL10220		ALUMINIUM	MECHANICAL CONNECTION
CL10405	MATT BLACK	ALUMINIUM	ELECTRIFIED MODULE 120cm
CL10430	MATT WHITE	ALUMINIUM	ELECTRIFIED MODULE 120cm
CL10505	MATT BLACK	ALUMINIUM	CONNECTION L
CL10530	MATT WHITE	ALUMINIUM	CONNECTION L
CL10605	MATT BLACK	ALUMINIUM	CONNECTION T
CL10630	MATT WHITE	ALUMINIUM	CONNECTION T
CL10705	MATT BLACK	ALUMINIUM	CONNECTION X
CL10730	MATT WHITE	ALUMINIUM	CONNECTION X





Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,15 Joule.



Earth wire . Fixture equipped with primary insulation only.



Beam 75°.



Product in conformity CE.



Colour rendering index >80.



Selectable colour temperature.



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.




Power supply included.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Non-replaceable light source.