


LISY RDX

- Adjustable round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency F.





















CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO460WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC100mA 36V	4,5W	3000K	600 Lm	474 Lm
DO460WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC100mA 36V	4,5W	3000K	600 Lm	474 Lm




MATT BLACK





MATT WHITE

-  Recessed ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.
-  Protection against an impact energy of 1 Joule.
-  Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.
-  Hole cut to insert luminaire. (58mm)
-  Minimum ceiling height to insert luminaire. (55mm)
-  Vertical orientation maximum to 20°.
-  Beam 36°.
-  Product in conformity CE.
-  CRI >80
-  LED specifications.
L70B50
50.000h
-  Photobiological risk RG1
-  Test on 650°.
-  Product can not be covered after installation even with insulation.
-  Class II power supply included.
-  Connect to a constant current Led power supply of 100mA DC.
-  The product is dimmable.

5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.