


LIVY R-230



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO239WW05	MATT BLACK	COMPOSITE	AC 230V	7W	3000K	800 Lm	440 Lm
DO239WW30	MATT WHITE	COMPOSITE	AC 230V	7W	3000K	800 Lm	615 Lm
DO239NW05	MATT BLACK	COMPOSITE	AC 230V	7W	4000K	850 Lm	475 Lm
DO239NW30	MATT WHITE	COMPOSITE	AC 230V	7W	4000K	850 Lm	655 Lm



NOIR MAT



BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,50 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (68mm)



Beam 90°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Luminaire with a 230V LED module.




3 years warranty.



Photometric data available on our website: www.indigo-lighting.com





Replaceable LED light source by an electrician.