


LOOP 2

- Spotlight for accent lighting for 48V track.
- Non dimmable.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
TR392WW05	MATT BLACK	ALUMINIUM	DC 48V	13W	3000K	1430 Lm	1220 Lm
TR392WW13	MATT BLACK - BRASS MATT	ALUMINIUM	DC 48V	13W	3000K	1430 Lm	1220 Lm
TR392WW14	MATT BLACK - MATT COPPER	ALUMINIUM	DC 48V	13W	3000K	1430 Lm	1220 Lm



MATT BLACK



MATT BLACK - BRASS
MATT



MATT BLACK - MATT
COPPER



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 2 Joules.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 38°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG0



Test on 650°.




Connect to a constant voltage LED power supply of 48VDC.



3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable LED light source by an electrician.