


LSA 1012 SX GU10 AUTO





COLOR	MATERIAL	SOCKET	AC	Watt Max	LAMP
CHROME	CAST ALUMINIUM	GU10 AUTO	AC 230V	50W	PAR16
WHITE	CAST ALUMINIUM	GU10 AUTO	AC 230V	50W	PAR16
BLACK	CAST ALUMINIUM	GU10 AUTO	AC 230V	50W	PAR16
MATT CHROME	CAST ALUMINIUM	GU10 AUTO	AC 230V	50W	PAR16
SATIN NICKEL	CAST ALUMINIUM	GU10 AUTO	AC 230V	50W	PAR16
	CHROME WHITE BLACK MATT CHROME	CHROME CAST ALUMINIUM WHITE CAST ALUMINIUM BLACK CAST ALUMINIUM MATT CHROME CAST ALUMINIUM	CHROME CAST ALUMINIUM GU10 AUTO WHITE CAST ALUMINIUM GU10 AUTO BLACK CAST ALUMINIUM GU10 AUTO MATT CHROME CAST ALUMINIUM GU10 AUTO	CHROMECAST ALUMINIUMGU10 AUTOAC 230VWHITECAST ALUMINIUMGU10 AUTOAC 230VBLACKCAST ALUMINIUMGU10 AUTOAC 230VMATT CHROMECAST ALUMINIUMGU10 AUTOAC 230V	CHROMECAST ALUMINIUMGU10 AUTOAC 230V50WWHITECAST ALUMINIUMGU10 AUTOAC 230V50WBLACKCAST ALUMINIUMGU10 AUTOAC 230V50WMATT CHROMECAST ALUMINIUMGU10 AUTOAC 230V50W









CHROME

BLANC

CHROME MAT

NOIR

NICKEL SATINE

Recessed ceiling mounting only. Indoor use only. 1 Protected against the ingress of solid bodies greater than 12 mm. Protected against rain. **IP** 23 IK Protection against an impact energy of 1 Joule. 06 Live parts are equipped with additional isolation protection, such as reinforced or double insulation. **75** Hole cut to insert luminaire (75mm) The luminaire can be adjusted vertically up to a maximum of 30°. 30° Product in conformity CE. CE Test on 650°. 650° Product can not be covered after installation even with insulation. 2 2 years warranty.



Replaceable light source by an end-user.

