


LUCKY 3 RDX



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO50605	MATT BLACK	ALUMINIUM	AC 230V	DC 260mA 37V	12W	2700-3000-4000K	1055 Lm (4000K)	845 Lm (4000K)
DO50630	MATT WHITE	ALUMINIUM	AC 230V	DC 260mA 37V	12W	2700-3000-4000K	1055 Lm (4000K)	845 Lm (4000K)



NOIR MAT



BLANC MAT



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (75mm)



Minimum ceiling height to insert luminaire. (60mm)



Vertical orientation maximum to 25°.



Beam 36°.



Product in conformity CE.



Colour rendering index >90.



Selectable colour temperature.



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Product can be covered after installation with insulation. (unrolled or blown)



Power supply included.



260
mA

Connect to a constant current Led power supply of 260mA DC.




The product is dimmable.

3


3 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.