OUTDOOR



LUXI 175 SENSOR

- Wall lamp for outdoor lighting.
- With 120° HF sensor, detetion zone adjustable to 8 m max.
- Opaline polycarbonate diffuser.
- Non-dimmable converter built in the device.

This product contains 72 light source(s)of energy efficiency E.




| CODE | COLOR | MATERIAL | AC | LED | T° (K) | LED Lumen | System Lumen |
|-----------|------------|-----------|---------|-----|--------|-----------|--------------|
| OU323WW24 | ANTHRACITE | ALUMINIUM | AC 230V | 9W | 3000K | 1260 Lm | 760 Lm |
| OU323WW30 | WHITE | ALUMINIUM | AC 230V | 9W | 3000K | 1260 Lm | 950 Lm |
| OU323NW24 | ANTHRACITE | ALUMINIUM | AC 230V | 9W | 4000K | 1300 Lm | 785 Lm |
| OU323NW30 | WHITE | ALUMINIUM | AC 230V | 9W | 4000K | 1300 Lm | 980 Lm |





ANTHRACITE

WHITE





Protected against dust, And protected against water spray.

Protection against an impact energy of 1 Joule.

Earth wire . Fixture equipped with primary insulation only.

Beam 105°.

Product in conformity CE.

CRI CRI>80

LED specifications. 50.000h

RG0 Photobiological risk RG0

650° Test on 650°.

Power supply included.

With sensor.

3 years warranty.

Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.

TECHNICAL DATA

OUTDOOR

WALL LIGHTS





Non-replaceable light source.