

## LUXI 193

- Rectangular outdoor recessed beacon wall light.

- Recessed box supplied.
- With cable inlet and outlet.
- Non dimmable converter built in the device.

This product contains 18 light source(s)of energy efficiency F.





CODE	COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
OU20424	ANTHRACITE	ALUMINIUM	AC 230V	6W	3000K	505 Lm	411 Lm
OU20447	CORTEN STEEL	ALUMINIUM	AC 230V	6W	3000K	505 Lm	411 Lm



Recessed wall mounting only. Indoor and outdoor use. 1 Protected against the ingress of dust. Protected against jets of water. **IP** 65 Protection against an impact energy of 5 Joules. IK 08 Earth wire . Fixture equipped with primary insulation only.  $\perp$ P Rectangular piercing to insert the luminaire. (190x233mm) 190x233 Beam 135°. 135° Product in conformity CE. CE **CRI** >80 CRI>80 LED specifications. L70B50 50.000h Photobiological risk RG0 RG0 Test on 650°. 650° Power supply included. R 3 3 years warranty. Photometric data available on our website: www.indigo-lighting.com @ Replaceable control gear by an electrician. ň

Replaceable LED light source by an electrician.