


# LUXI 80

- Round terminal for outdoor lighting.
- Opaline polycarbonate diffuser.
- Non-dimmable converter built in the device.

This product contains 72 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
OU324WW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	18W	3000K	2340 Lm	1325 Lm	900
OU324NW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	18W	4000K	2410 Lm	1750 Lm	900
OU325WW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	18W	3000K	2340 Lm	1325 Lm	2200
OU325NW24	ANTHRACITE	CAST ALUMINIUM	AC 230V	18W	4000K	2410 Lm	1750 Lm	2200



Floor mounting only.



Outdoor use.



Protected against dust, And protected against water spray.



Protection against an impact energy of 5 Joules.



Earth wire . Fixture equipped with primary insulation only.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG0



Test on 650°.




Power supply included.




3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.