


LUZ 2

- Ceiling for outdoor lighting.
- 2700K, 3000K or 4000K as desired via a switch in the luminaire.
- Glass diffuser.
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency G.



















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
OU49005	MATT BLACK	ALUMINIUM	AC 230V	20W	2700-3000-4000K	1930 Lm (4000K)	1475 Lm (4000K)
OU49030	MATT WHITE	ALUMINIUM	AC 230V	20W	2700-3000-4000K	1930 Lm (4000K)	1485 Lm (4000K)





MATT BLACK



MATT WHITE

-  Ceiling mounting only.
-  Indoor and outdoor use.
-  Protected against dust, And protected against water spray.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Beam 40°.
-  Product in conformity CE.
-  CRI>90
-  3 CCT.
2700K
3000K
4000K
-  LED specifications.
L80B10
50.000h
-  UGR below 19.
-  Photobiological risk RG1
-  Test on 850°.
-  Power supply included.
-  5 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.