


# LYON 1 R

- Fixed round recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote DALI-push non-dimmable or dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
<b>NOT DIMMABLE</b>								
DO538WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1515 Lm
DO538WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1590 Lm
DO538WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1590 Lm
DO538WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1590 Lm
DO538NW05	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1545 Lm
DO538NW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1625 Lm
DO538NW30	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1625 Lm
DO538NW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1625 Lm
<b>DALI DIMMABLE</b>								
DO538WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1515 Lm
DO538WW17DA	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1590 Lm
DO538WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1590 Lm
DO538WW53DA	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	3000K	1875 Lm	1590 Lm
DO538NW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1545 Lm
DO538NW17DA	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1625 Lm
DO538NW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1625 Lm
DO538NW53DA	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 350mA 36V	15W	4000K	1920 Lm	1625 Lm



MATT BLACK




MATT BLACK - SILVER





MATT WHITE





MATT WHITE - SILVER


 Recessed ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.

 Protection against an impact energy of 1 Joule.

 Live parts are equipped with additional isolation protection, such as reinforced or double insulation.

 Hole cut to insert luminaire (95mm)

 Minimum ceiling height to insert luminaire. (100mm)



Beam 60°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.




Connect to a constant current Led power supply of 350mA DC.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.