


# LYON 2 R

- Fixed round recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote  
DALI-push non-dimmable or dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
<b>NOT DIMMABLE</b>								
DO539WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2535 Lm
DO539WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2670 Lm
DO539WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2670 Lm
DO539WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2670 Lm
DO539NW05	MATT BLACK	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2590 Lm
DO539NW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2750 Lm
DO539NW30	MATT WHITE	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2750 Lm
DO539NW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2750 Lm
<b>DALI DIMMABLE</b>								
DO539WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2535 Lm
DO539WW17DA	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2670 Lm
DO539WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2670 Lm
DO539WW53DA	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	3000K	3000 Lm	2670 Lm
DO539NW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2590 Lm
DO539NW17DA	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2750 Lm
DO539NW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2750 Lm
DO539NW53DA	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 600mA 36V	25W	4000K	3070 Lm	2750 Lm



MATT BLACK




MATT BLACK - SILVER





MATT WHITE





MATT WHITE - SILVER


 Recessed ceiling mounting only.


 Indoor use only.

 Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.

 Protection against an impact energy of 1 Joule.

 Live parts are equipped with additional isolation protection, such as reinforced or double insulation.

 Hole cut to insert luminaire. (125mm)

 Minimum ceiling height to insert luminaire. (120mm)



Beam 60°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.




Connect to a constant current Led power supply of 600mA DC.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.