


# LYON 3 R

- Fixed round recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote DALI-push non-dimmable or dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



| CODE                 | COLOR               | MATERIAL  | AC      | DC           | LED | T° (K) | LED Lumen | System Lumen |
|----------------------|---------------------|-----------|---------|--------------|-----|--------|-----------|--------------|
| <b>NOT DIMMABLE</b>  |                     |           |         |              |     |        |           |              |
| DO540WW05            | MATT BLACK          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3020 Lm      |
| DO540WW17            | MATT BLACK - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3180 Lm      |
| DO540WW30            | MATT WHITE          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3180 Lm      |
| DO540WW53            | MATT WHITE - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3180 Lm      |
| DO540NW05            | MATT BLACK          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3085 Lm      |
| DO540NW17            | MATT BLACK - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3275 Lm      |
| DO540NW30            | MATT WHITE          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3275 Lm      |
| DO540NW53            | MATT WHITE - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3275 Lm      |
| <b>DALI DIMMABLE</b> |                     |           |         |              |     |        |           |              |
| DO540WW05DA          | MATT BLACK          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3020 Lm      |
| DO540WW17DA          | MATT BLACK - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3180 Lm      |
| DO540WW30DA          | MATT WHITE          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3180 Lm      |
| DO540WW53DA          | MATT WHITE - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 3000K  | 4000 Lm   | 3180 Lm      |
| DO540NW05DA          | MATT BLACK          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3085 Lm      |
| DO540NW17DA          | MATT BLACK - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3275 Lm      |
| DO540NW30DA          | MATT WHITE          | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3275 Lm      |
| DO540NW53DA          | MATT WHITE - SILVER | ALUMINIUM | AC 230V | DC 800mA 36V | 30W | 4000K  | 4100 Lm   | 3275 Lm      |



- Recessed ceiling mounting only.
- Indoor use only.
- Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.
- Protection against an impact energy of 1 Joule.
- Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
- Hole cut to insert luminaire (150 mm)
- Minimum ceiling height to insert luminaire. (135mm)



Beam 60°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.




Connect to a constant current Led power supply of 800mA DC.




5 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.