


LYON 4 R

- Fixed round recessed downlight.
- Low luminance reflector.
- Fastened with springs.
- Remote
DALI-push non-dimmable and dimmable converter supplied.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
NOT DIMMABLE								
DO541WW05	MATT BLACK	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	3835 Lm
DO541WW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	4035 Lm
DO541WW30	MATT WHITE	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	4035 Lm
DO541WW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	4035 Lm
DO541NW05	MATT BLACK	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	3915 Lm
DO541NW17	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	4160 Lm
DO541NW30	MATT WHITE	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	4160 Lm
DO541NW53	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	4160 Lm
DALI DIMMABLE								
DO541WW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	3835 Lm
DO541WW17DA	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	4035 Lm
DO541WW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	4035 Lm
DO541WW53DA	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	3000K	5000 Lm	4035 Lm
DO541NW05DA	MATT BLACK	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	3915 Lm
DO541NW17DA	MATT BLACK - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	4160 Lm
DO541NW30DA	MATT WHITE	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	4160 Lm
DO541NW53DA	MATT WHITE - SILVER	ALUMINIUM	AC 230V	DC 1050mA 36V	40W	4000K	5120 Lm	4160 Lm



- Recessed ceiling mounting only.
- Indoor use only.
- Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.
- Protection against an impact energy of 1 Joule.
- Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
- Hole cut to insert luminaire (175 mm)
- Minimum ceiling height to insert luminaire. (145mm)



Beam 60°.



Product in conformity CE.



CRI>90



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 850°.



Product can not be covered after installation even with insulation.



Power supply included.




Connect to a constant current Led power supply of 1050mA DC.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.