

## **MANYL 1**

- Adjustable round ceiling lamp.
- Dimmable converter built in in the device.
- Compatible with start and end-of-phase dimmer.
- This product contains 1 light source(s) of energy efficiency G.





TERIAL AC	LED T° (K)	LED Lumen	System Lumen
IMINIUM AC 230V	5W 3000K	770 Lm	449 Lm
IMINIUM AC 230V	5W 3000K	770 Lm	449 Lm



MATT BLACK



	Ceiling mounting only.
	Indoor use only.
<b>IP</b> 20	Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
<b>IK</b> 02	Protection against an impact energy of 0,20 Joule.
	Earth wire . Fixture equipped with primary insulation only.
<b>ノ</b> 90°	Vertical orientation maximum to 90°.
⊖ 355°	Horizontal orientation maximum to 355°.
<mark>∕</mark> 36°	Beam 36°.
CE	Product in conformity CE.
<b>CRI</b> >90	CRI>90
LED L70B50 50.000h	LED specifications.
RG1	Photobiological risk RG1
650°	Test on 650°.
ž.	Power supply included.
	The product is dimmable.
3	3 years warranty.
0	Photometric data available on our website: www.indigo-lighting.com

## INDOOR

## **CEILING LIGHTS**



Replaceable control gear by an electrician.

Replaceable LED light source by an electrician.

