


# MANYL 2

- Adjustable round wall lamp.
- Dimmable converter built in in the device.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.




















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA210WW16	MATT BLACK	ALUMINIUM	AC 230V	11W	3000K	1180 Lm	938 Lm
WA210WW21	MATT WHITE	ALUMINIUM	AC 230V	11W	3000K	1180 Lm	938 Lm



MATT BLACK



MATT WHITE

-  Ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 355°.
-  Beam 36°.
-  Product in conformity CE.
-  CRI>90
-  LED specifications.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  The product is dimmable.
-  3 years warranty.
-  Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.