


# MARY RDX-230

- Adjustable round recessed spotlight.
- Fastened with springs.
- Can be covered with peeled insulation.
- Automatic double terminal block.
- Does not require a converter.
- Dimmable.
- Compatible with end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
DO315WW05	MATT BLACK	COMPOSITE	AC 230V	7,5W	3000K	750 Lm	600 Lm
DO315WW30	MATT WHITE	COMPOSITE	AC 230V	7,5W	3000K	750 Lm	600 Lm
DO315NW05	MATT BLACK	COMPOSITE	AC 230V	7,5W	4000K	770 Lm	615 Lm
DO315NW30	MATT WHITE	COMPOSITE	AC 230V	7,5W	4000K	770 Lm	615 Lm



MATT BLACK



MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (75mm)



The luminaire can be adjusted vertically up to a maximum of 30°.



Beam 60°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.



Product can be covered after installation with insulation. (not blown)



Luminaire with a 230V LED module.




The product is dimmable.



3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.