


MILO 1

- Decorative wall lamp.
- Exposed base with switch.
- Non dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA11205	MATT BLACK	ALUMINIUM	AC 230V	5W	3000K	500 Lm	405 Lm
WA11230	MATT WHITE	ALUMINIUM	AC 230V	5W	3000K	500 Lm	450 Lm
WA11263	BRUSHED BRASS	ALUMINIUM	AC 230V	5W	3000K	500 Lm	405 Lm



















MATT BLACK





MATT WHITE



BRUSHED BRASS

-  Wall mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 355°.
-  Beam 40°.
-  Product in conformity CE.
-  CRI>90
-  LED specifications.
L80B50
50.000h
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  3 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.