


MILO 2

- Decorative wall lamp.
- Exposed base with switch for three levels of lighting (25%, 50% and 100%) and two USB sockets (5VDC, 2A).
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency F.



| CODE | COLOR | MATERIAL | AC | LED | T° (K) | LED Lumen | System Lumen |
|-----------|------------|-----------|---------|-----|--------|-----------|--------------|
| WA165WW05 | MATT BLACK | ALUMINIUM | AC 230V | 5W | 3000K | 500 Lm | 405 Lm |
| WA165WW30 | MATT WHITE | ALUMINIUM | AC 230V | 5W | 3000K | 500 Lm | 450 Lm |



MATT BLACK



MATT WHITE



Wall mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 180°.



Beam 40°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.



With USB plug.




3 years warranty.




Photometric data available on our website: www.indigo-lighting.com





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.