


MILO 3

- Decorative wall lamp.
- Semi-recessed base.
- With dimmer switch
- .
- Supplied with dimmable converter.
- Mounting in a standard recessed box (not supplied).

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA215SW05	MATT BLACK	ALUMINIUM	AC 230V	5W	2700K	460 Lm	395 Lm
WA215SW30	MATT WHITE	ALUMINIUM	AC 230V	5W	2700K	460 Lm	395 Lm
WA215SW63	BRUSHED BRASS	ALUMINIUM	AC 230V	5W	2700K	460 Lm	395 Lm





















MATT BLACK




MATT WHITE




BRUSHED BRASS

-  Recessed wall mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Hole cut to insert luminaire (68mm)
-  Vertical orientation maximum to 90°.
-  Horizontal orientation maximum to 330°.
-  Beam 40°.
-  Product in conformity CE.
-  CRI>90
-  LED specifications.
L80B50
50.000h
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  With dimmer switch.
-  3 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com





Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.