


MINI 6

- Mini round floor recessed mount.
- White (3000K, 6000K) or blue (BL) LED.
- 1.50m cable supplied.
- 12 VDC converter to be ordered separately.
- Max. 80 MINI 6 by CD171.



This product contains 1 light source(s) of energy efficiency N/A.

CODE	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
KO91WW	ALUMINIUM	DC 12V	0,12W	3000K	15 Lm	6 Lm
KO91CL	ALUMINIUM	DC 12V	0,12W	6000K	15 Lm	6 Lm
KO91BL	ALUMINIUM	DC 12V	0,12W	BL	-	-

CODE	Watt Max	PRI	SEC	INPUTS	OUTPUTS	Max Case T°	Max Amb. T°
CD171	0-20W	AC 230V	DC 12V	1	1	90°C	40°C



Recessed floor mounting only.



Recessed wall mounting only.



Indoor and outdoor use.



Protected against the ingress of dust. Protected against jets of water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (14 mm)



Beam 90°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply not included.



Parallel connection.



Connect to a constant voltage LED power supply of 12VDC.



3 years warranty.

