


# MOON

- Portable luminaire.
- With switch for three levels of lighting (25%, 50% and 100%) and rechargeable battery via USB socket.
- Charging time 5 hours with autonomy of 5 hours at 100%, 10 hours at 50% and 20 hours at 25% luminosity.
- Supplied with USB cable, without charger.
- The magnetic base is supplied with a double-sided sticker for all surfaces and 2 screws.
- Base and charger to be ordered separately.



This product contains 1 light source(s) of energy efficiency E.

CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
WA204WW30	MATT WHITE	ALUMINIUM	DC 3,7V	1,5W	2700K	170 Lm	100 Lm
WA204WW05	MATT BLACK	ALUMINIUM	DC 3,7V	1,5W	2700K	170 Lm	100 Lm
WA204WW03	CHROME	ALUMINIUM	DC 3,7V	1,5W	2700K	170 Lm	100 Lm
WA204WW88	BRUSHED COPPER	ALUMINIUM	DC 3,7V	1,5W	2700K	170 Lm	100 Lm



MATT WHITE








MATT BLACK



CHROME



BRUSHED COPPER

ACCESSOIRES	COLOR	DESCRIPTION	
WA20505	BLACK	BASE WITH MAGNET	
WA20605	BLACK	BASE FOR OFFICE LAMP	
WA20703	CHROME	BASE + SUSPENSION 2m	
WA20804	WHITE	USB CHARGER	
OU42304	WHITE	MULTI USB CHARGER (8 PORTS)	



Mobile.



Wall and ceiling mounting only.



Suspended mounting only.



Indoor and outdoor use.



Protected against the ingress of solid bodies greater than 1mm. Protected against splashing water.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Product in conformity CE.



**CRI**  
>80

CRI>80

**LED**  
L70B50  
50,000h

LED specifications.

**RG0**

Photobiological risk RG0

**650°**


Test on 650°.

**USB**

Rechargeable battery via USB plug.

**3**

3 years warranty.

 Non-replaceable light source.