


MOWI RD

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.
- Remote dimmable converter supplied.
- Compatible with start and end-of-phase dimmer.

This product contains 1 light source(s) of energy efficiency G.



CODE	COLOR	MATERIAL	AC	DC	LED	T° (K)	LED Lumen	System Lumen
DO467WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	DC 260mA 18V	6W	3000K	550 Lm	295 Lm
DO467WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	DC 260mA 18V	6W	3000K	550 Lm	295 Lm



MATT BLACK

MATT WHITE



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater than 12 mm. Protected against rain.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Hole cut to insert luminaire (45 mm)



Minimum ceiling height to insert luminaire. (115mm)



Beam 36°.



Product in conformity CE.



CRI >80



LED specifications.



UGR below 19.



Photobiological risk RG1



Test on 650°.



Product can not be covered after installation even with insulation.



Class II power supply included.




Connect to a constant current Led power supply of 260mA DC.





The product is dimmable.



5 5 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.