
## TECHNICAL DATA INDOOR SUSPENSIONS



## NOVA CSP 1 P

This product contains 1 light source(s) of energy efficiency D.





CODE	COLOR	MATERIAL	AC	LED	Т° (К)	LED Lumen	System Lumen
SU17036	MATT BLACK - GOLD	ALUMINIUM	AC 230V	26W	2700-3000-4000K	3930 Lm (4000K)	3000 Lm (4000K)
SU17080	MATT WHITE - GOLD	ALUMINIUM	AC 230V	26W	2700-3000-4000K	3930 Lm (4000K)	3000 Lm (4000K)
MATT BLACK - GO							
ACCESSOIRES	MATERIAL	DESCRIPT	ION				
NV45UPM	POLYCARBON	ATE UPLIGHT KIT	NOVA 1 13W 3000K 11	00Lm			0
Suspended	d mounting only.						<b>*</b>
Indoor use	only.						
<b>IP</b> 40 Protected a ingress of	against the ingress of so liquids.	lid bodies greater tha	n 1mm. No protection	against the			
IK Protection	against an impact energ	y of 1 Joule.					
Live parts insulation.	are equipped with addition	onal isolation protection	on, such as reinforced	l or double			
Beam 120°							
CE	conformity CE.						
>80	dering index >80.						
2700K 3000K 4000K	colour temperature.						
LED LED specif	fications.						
UGR UGR below <19	w 19.						
Power sup	ply included.						
The produc	ct is dimmable (1-10V).						
DALI PUSH	ct is dimmable (DALI inp	out + push-dim).					
5 years wa	rranty.						

## INDOOR

## SUSPENSIONS



Replaceable control gear by an electrician.

Replaceable LED light source by an electrician.

