


NOVA CSP 2 P

This product contains 1 light source(s) of energy efficiency D.


















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
SU17136	MATT BLACK - GOLD	ALUMINIUM	AC 230V	40W	2700-3000-4000K	6075 Lm (4000K)	4800 Lm (4000K)
SU17180	MATT WHITE - GOLD	ALUMINIUM	AC 230V	40W	2700-3000-4000K	6075 Lm (4000K)	4800 Lm (4000K)




MATT BLACK - GOLD MATT WHITE - GOLD


ACCESSOIRES	MATERIAL	DESCRIPTION
NV60UPM	POLYCARBONATE	UPLIGHT KIT NOVA 2 20W 3000K 1700Lm



-  Suspended mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater than 1mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 1 Joule.
-  Live parts are equipped with additional isolation protection, such as reinforced or double insulation.
-  Beam 120°.
-  Product in conformity CE.
-  Colour rendering index >80.
-  Selectable colour temperature.
2700K
3000K
4000K
-  LED specifications.
L70B10
50,000h
-  UGR below 19.
-  Power supply included.
-  The product is dimmable (1-10V).
-  The product is dimmable (DALI input + push-dim).
-  5 years warranty.



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.