


# ONEX

- Luminaire for accent lighting for 48V track.
- Wall washer.

This product contains 1 light source(s) of energy efficiency F.



| CODE                 | COLOR        | MATERIAL  | DC     | LED | T° (K) | LED Lumen | System Lumen |
|----------------------|--------------|-----------|--------|-----|--------|-----------|--------------|
| <b>NOT DIMMABLE</b>  |              |           |        |     |        |           |              |
| TR283WW05            | ■ MATT BLACK | ALUMINIUM | DC 48V | 12W | 3000K  | 1030 Lm   | 526 Lm       |
| TR283NW05            | ■ MATT BLACK | ALUMINIUM | DC 48V | 12W | 4000K  | 1270 Lm   | 594 Lm       |
| <b>DALI DIMMABLE</b> |              |           |        |     |        |           |              |
| TR283WW05DA          | ■ MATT BLACK | ALUMINIUM | DC 48V | 12W | 3000K  | 1030 Lm   | 526 Lm       |
| TR283NW05DA          | ■ MATT BLACK | ALUMINIUM | DC 48V | 12W | 4000K  | 1270 Lm   | 594 Lm       |



Wall and ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG1



Test on 650°.




Connect to a constant voltage LED power supply of 48VDC.



3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.