

OSIS 1

- Spotlight for accent lighting.
- Adapter for Track III SURFACE.
- Non-dimmable converter built in the device (TR370).
- TR384 with adapter compatible with the CASAMBI application.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
NOT DIMMABLE							
TR370WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	25W	3000K	2600 Lm	1783 Lm
TR370WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	25W	3000K	2600 Lm	2002 Lm
TR370NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	25W	4000K	2700 Lm	1791 Lm
TR370NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	25W	4000K	2700 Lm	2086 Lm
COMPATIBLE WITH THE CASAMBI APPLICATION							
TR384WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	25W	3000K	2600 Lm	1783 Lm
TR384WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	25W	3000K	2600 Lm	2002 Lm
TR384NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	25W	4000K	2700 Lm	1791 Lm
TR384NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	25W	4000K	2700 Lm	2086 Lm



MATT BLACK

MATT WHITE



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 1 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 60°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG1



Test on 850°.




Power supply included.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.