

OSIS 1 PLUS

- Spotlight for accent lighting.
- Adapter for Track III SURFACE.
- 2700K, 3000K or 4000K selectable via a switch on the adapter.
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency F.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR43805	MATT BLACK	CAST ALUMINIUM	AC 230V	25W	2700-3000-4000K	3200 Lm (4000K)	2100 Lm (4000K)
TR43830	MATT WHITE	CAST ALUMINIUM	AC 230V	25W	2700-3000-4000K	3200 Lm (4000K)	2210 Lm (4000K)



MATT BLACK

MATT WHITE



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 1 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 60°.



Product in conformity CE.



Colour rendering index >90.



Selectable colour temperature.



LED specifications.



Photobiological risk RG1



Test on 850°.




Power supply included.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.