

OSIS 2

- Spotlight for accent lighting.
- Adapter for Track III SURFACE.
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency E.



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
TR371WW05	MATT BLACK	CAST ALUMINIUM	AC 230V	40W	3000K	4400 Lm	2360 Lm
TR371WW30	MATT WHITE	CAST ALUMINIUM	AC 230V	40W	3000K	4400 Lm	2985 Lm
TR371NW05	MATT BLACK	CAST ALUMINIUM	AC 230V	40W	4000K	4700 Lm	2840 Lm
TR371NW30	MATT WHITE	CAST ALUMINIUM	AC 230V	40W	4000K	4700 Lm	3617 Lm



MATT BLACK

MATT WHITE



Ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 1 Joule.



Earth wire . Fixture equipped with primary insulation only.



Vertical orientation maximum to 90°.



Horizontal orientation maximum to 350°.



Beam 60°.



Product in conformity CE.



CRI>90



LED specifications.



Photobiological risk RG1



Test on 850°.




Power supply included.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.