




# PARA

- Terminal with solar cells and rechargeable battery.
- Works only when the luminosity is less than 20 Lux.
- 120° RI sensor, max. detection distance 6m.
- Three modes
  - ON  
100% luminosity for 6 hours without detection
  - DIM  
20% luminosity for 4 hours, when movement is detected, le luminaire switches to 100% luminosity for 15 seconds than to 20% luminosity
  - AUTO  
when movement is detected the light turns on at 100% luminosity for 15 seconds then turns off.
- Charging time 8 hours in full sunlight.
- Stake to be buried included.



CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen
OU435WW24	ANTHRACITE	CAST ALUMINIUM	DC 3,7V	1W	3000K	110 Lm	73 Lm

ACCESSOIRES	DESCRIPTION	
OU446	REPLACEMENT BATTERY	
OU469	REPLACEMENT GROUND SPIKE	



Floor mounting only.



Outdoor use.



Protected against dust, And protected against water spray.



Protection against an impact energy of 1 Joule.



Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.



Vertical orientation maximum to 15°.



Product in conformity CE.



CRI>80



LED specifications.



Photobiological risk RG0



Test on 650°.



With solar cells.



With sensor.



3 years warranty.

