





PARO 2


- Spotlight for accent lighting for 48V track.


This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α
NOT DIMMABLE								
TR289SW05	MATT BLACK	ALUMINIUM	DC 48V	14W	2700K	1250 Lm	943 Lm	15°
TR289WW05	MATT BLACK	ALUMINIUM	DC 48V	14W	3000K	1380 Lm	1014 Lm	15°
TR289NW05	MATT BLACK	ALUMINIUM	DC 48V	14W	4000K	1500 Lm	1090 Lm	15°
TR288SW05	MATT BLACK	ALUMINIUM	DC 48V	14W	2700K	1250 Lm	984 Lm	30°
TR288WW05	MATT BLACK	ALUMINIUM	DC 48V	14W	3000K	1380 Lm	1054 Lm	30°
TR288NW05	MATT BLACK	ALUMINIUM	DC 48V	14W	4000K	1500 Lm	1120 Lm	30°
TR287SW05	MATT BLACK	ALUMINIUM	DC 48V	14W	2700K	1250 Lm	974 Lm	50°
TR287WW05	MATT BLACK	ALUMINIUM	DC 48V	14W	3000K	1380 Lm	1151 Lm	50°
TR287NW05	MATT BLACK	ALUMINIUM	DC 48V	14W	4000K	1500 Lm	1198 Lm	50°
DALI DIMMABLE								
TR289WW05DA	MATT BLACK	ALUMINIUM	DC 48V	14W	3000K	1380 Lm	1014 Lm	15°
TR289NW05DA	MATT BLACK	ALUMINIUM	DC 48V	14W	4000K	1500 Lm	1090 Lm	15°
TR288WW05DA	MATT BLACK	ALUMINIUM	DC 48V	14W	3000K	1380 Lm	1054 Lm	30°
TR288NW05DA	MATT BLACK	ALUMINIUM	DC 48V	14W	4000K	1500 Lm	1120 Lm	30°
TR287WW05DA	MATT BLACK	ALUMINIUM	DC 48V	14W	3000K	1380 Lm	1151 Lm	50°
TR287NW05DA	MATT BLACK	ALUMINIUM	DC 48V	14W	4000K	1500 Lm	1198 Lm	50°


ACCESSOIRES	COLOR	DESCRIPTION	
TR29005	BLACK	SNOOT	
TR29105	BLACK	WALL WASHER	
TR29337		FROSTED RING	
TR29437		FROSTED DIFFUSER	
TR29537		BLADE OF LIGHT	
TR29605	BLACK	HONEYCOMB	


 Wall and ceiling mounting only.


 Indoor use only.


 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

 Protection against an impact energy of 0,20 Joule.


 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.


 Vertical orientation maximum to 90°.


 Horizontal orientation maximum to 355°.


 Product in conformity CE.


 CRI>80


 LED specifications.


 Photobiological risk RG1

 Test on 850°.

 Connect to a constant voltage LED power supply of 48VDC.

 3 years warranty.

 Photometric data available on our website: www.indigo-lighting.com

 Replaceable LED light source by an electrician.