


# PARO 3


- Spotlight for accent lighting, for 48V track.


This product contains 1 light source(s) of energy efficiency F.





CODE	COLOR	MATERIAL	DC	LED	T° (K)	LED Lumen	System Lumen	α
<b>NOT DIMMABLE</b>								
TR300WW05	MATT BLACK	ALUMINIUM	DC 48V	35W	3000K	3820 Lm	2840 Lm	30°
TR300NW05	MATT BLACK	ALUMINIUM	DC 48V	35W	4000K	4200 Lm	3100 Lm	30°
TR299WW05	MATT BLACK	ALUMINIUM	DC 48V	35W	3000K	3820 Lm	2930 Lm	50°
TR299NW05	MATT BLACK	ALUMINIUM	DC 48V	35W	4000K	4200 Lm	3215 Lm	50°
<b>DALI DIMMABLE</b>								
TR300WW05DA	MATT BLACK	ALUMINIUM	DC 48V	28W	3000K	3400 Lm	2523 Lm	30°
TR300NW05DA	MATT BLACK	ALUMINIUM	DC 48V	28W	4000K	3700 Lm	2871 Lm	30°
TR299WW05DA	MATT BLACK	ALUMINIUM	DC 48V	28W	3000K	3400 Lm	2542 Lm	50°
TR299NW05DA	MATT BLACK	ALUMINIUM	DC 48V	28W	4000K	3700 Lm	2925 Lm	50°


ACCESSOIRES	COLOR	DESCRIPTION	
TR30105	BLACK	SNOOT	
TR30205	BLACK	WALL WASHER	
TR30337		FROSTED RING	
TR30437		FROSTED DIFFUSER	
TR30537		BLADE OF LIGHT	
TR30605	BLACK	HONEYCOMB	


 Wall and ceiling mounting only.

 Indoor use only.

 Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.

 Protection against an impact energy of 0,20 Joule.

 Product can be connected to low-voltage systems. A safety extra low voltage luminaire in which voltages higher than those of SELV are not generated.

 Vertical orientation maximum to 90°.



Horizontal orientation maximum to 355°.



Product in conformity CE.



CRI >80



LED specifications.



Photobiological risk RG1



Test on 850°.




Connect to a constant voltage LED power supply of 48VDC.



3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Replaceable LED light source by an electrician.