


PIXA 2

- Adjustable wall or ceiling lamp.
- Dimmable converter built in in the device.
- Compatible with end-of-phase dimmer.

This product contains 2 light source(s) of energy efficiency G.




















CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
WA13305	MATT BLACK	CAST ALUMINIUM	AC 230V	2x10W	3000K	2x1200 Lm	2x744 Lm
WA13330	MATT WHITE	CAST ALUMINIUM	AC 230V	2x10W	3000K	2x1200 Lm	2x744 Lm



MATT BLACK



MATT WHITE

-  Wall and ceiling mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 0,20 Joule.
-  Earth wire . Fixture equipped with primary insulation only.
-  Vertical orientation maximum to 175°.
-  Horizontal orientation maximum to 355°.
-  Beam 38°.
-  Product in conformity CE.
-  CRI>80
-  LED specifications.
-  Photobiological risk RG1
-  Test on 650°.
-  Power supply included.
-  The product is dimmable.
-  2 years warranty.
-  Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.