


# PLANK 1

- Decorative wall lamp.
  - Opaline polycarbonate diffuser.
  - Indirect lighting.
  - Non-dimmable converter built in the device.
- This product contains 1 light source(s) of energy efficiency E.


















| CODE         | COLOR      | MATERIAL  | AC      | LED | T° (K) | LED Lumen | System Lumen | L (mm) |
|--------------|------------|-----------|---------|-----|--------|-----------|--------------|--------|
| PK30/1A/3K/W | MATT WHITE | ALUMINIUM | AC 230V | 20W | 3000K  | 2520 Lm   | 1760 Lm      | 300    |
| PK30/1A/4K/W | MATT WHITE | ALUMINIUM | AC 230V | 20W | 4000K  | 2730 Lm   | 1910 Lm      | 300    |
| PK60/1A/3K/W | MATT WHITE | ALUMINIUM | AC 230V | 40W | 3000K  | 5400 Lm   | 3775 Lm      | 600    |
| PK60/1A/4K/W | MATT WHITE | ALUMINIUM | AC 230V | 40W | 4000K  | 5850 Lm   | 4090 Lm      | 600    |




MATT WHITE

MATT WHITE

-  Wall mounting only.
-  Indoor use only.
-  Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.
-  Protection against an impact energy of 20 Joules.
-  Earth wire . Fixture equipped with primary insulation only.
-  Beam 110°.
-  Product in conformity CE.
-  Colour rendering index >90.
-  LED specifications.
-  Photobiological risk RG0
-  Test on 650°.
-  Power supply included.
-  5 years warranty.
-  Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)

 Replaceable control gear by an electrician.

 Replaceable LED light source by an electrician.