


PLANK 2

- Decorative wall lamp.
- Opaline polycarbonate diffusers.
- Direct/indirect lighting.
- Non-dimmable converter built in the device.

This product contains 2 light source(s) of energy efficiency E(3000K), D(4000K).



CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
PK30/2A/3K/W	MATT WHITE	ALUMINIUM	AC 230V	2x16W	3000K	2x1980 Lm	2x1105 Lm	300
PK30/2A/4K/W	MATT WHITE	ALUMINIUM	AC 230V	2x16W	4000K	2x2145 Lm	2x1200 Lm	300
PK60/2A/3K/W	MATT WHITE	ALUMINIUM	AC 230V	2x32W	3000K	2x4030 Lm	2x2820 Lm	600
PK60/2A/4K/W	MATT WHITE	ALUMINIUM	AC 230V	2x32W	4000K	2x4370 Lm	2x3055 Lm	600



MATT WHITE

MATT WHITE



Wall mounting only. This lamp illuminates on 2 areas.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 20 Joules.



Earth wire . Fixture equipped with primary insulation only.



Beam 110°.



Product in conformity CE.



Colour rendering index >90.



LED specifications.



Photobiological risk RG0



Test on 650°.




Power supply included.




5 years warranty.



Photometric data available on our website: www.indigo-lighting.com



Replaceable control gear by an electrician.



Replaceable LED light source by an electrician.