LED BATTEN LIGHTS



POLARIS


- Waterproof linear luminaire.
- Polycarbonate diffuser.
- With through-wiring.

This product contains 1 light source(s) of energy efficiency E.



		○ ♦ 66,5
L=1200	L=1500	70,5
POL112N	POL115N	
POL212N	POL215N	

CODE	COLOR	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen	L (mm)
POL112N	WHITE	POLYCARBONATE	AC 230V	20W	4000K	2790 Lm	2600 Lm	1200
POL212N	WHITE	POLYCARBONATE	AC 230V	34W	4000K	4940 Lm	4700 Lm	1200
POL115N	WHITE	POLYCARBONATE	AC 230V	30W	4000K	4190 Lm	4000 Lm	1500
POL215N	WHITE	POLYCARBONATE	AC 230V	50W	4000K	7270 Lm	6750 Lm	1500



Indoor use only.

Protected against penetration of dust Protected against water jets.

Protection against an impact energy of 20 Joules.

Live parts are equipped with additional isolation protection, such as reinforced or double insulation.

Beam 130°.

Product in conformity CE.

CRI Colour rendering index >80.

LED LED specifications.

RG0 Photobiological risk RG0

650° Test on 650°.

Power supply included.

5 years warranty.

Photometric data available on our website: www.indigo-lighting.com

Non-replaceable control gear.

Non-replaceable light source.