


# PURE 380

- Round floor recessed fixture.
- Carriage resistance 1200kg.
- Recessed box at 0.50m cable supplied .
- Non-dimmable converter built in the device.

This product contains 1 light source(s) of energy efficiency G.



CODE	MATERIAL	AC	LED	T° (K)	LED Lumen	System Lumen
PU637WW	STAINLESS STEEL 316	AC 230V	7W	3000K	540 Lm	393 Lm
OU263NW16	STAINLESS STEEL 316	AC 230V	7W	4000K	620 Lm	483 Lm



Recessed floor mounting only.



Indoor and outdoor use.



Dust-tight. Watertight (immersible).



Protection against an impact energy of 1 Joule.



Earth wire . Fixture equipped with primary insulation only.



Hole cut to insert luminaire (75mm)



Hole cut to insert recessed housing. (105mm).



Beam 40°.



Product in conformity CE.



Colour rendering index >80.



LED specifications.



Photobiological risk RG1



Test on 650°.



Power supply included.




Clean regularly with a suitable product to prevent corrosion. No mordant or abrasive material.




3 years warranty.



Photometric data available on our website: [www.indigo-lighting.com](http://www.indigo-lighting.com)



Non-replaceable light source.



Non-replaceable control gear.